



### Typical Inspection Data:

Density @ 20°C	0.833 g/cm <sup>3</sup>
Viscosity @ 40°C	26.2 cSt
Viscosity @ 100°C	6.10 cSt
Colour	Straw
Flash Point	220°C
Pour point	-69°C
Viscosity Index	194
Phosphorus	0.02%

## EXT Fluid

### Central Hydraulic Fluid

#### Recommended by Comma for applications requiring:

GM 89021185 / GM 89021186, GM 1052884 / GM 993294, GM 19329450 / GM 19329451, GM 1940707, GM 89020661; Hyundai / Kia PSF-3, PSF-4; Chrysler MS 5931; Fiat 9.55550-AG1, AG2, AG3 ISO VG 22, AV4; Texaco Cold Climate Power Steering Fluid; Saab P/N 45 30 09 800; Dia-Queen PSF; Pentosin CHF 7.1; Toyota Type EH; Nissan PSF-II; PSA S71 2710

#### Product Features:

- EXT Fluid is a special synthetic based hydraulic fluid suitable for central hydraulic systems, power steering and suspension level control systems.
- Also suitable for certain stability and traction control systems, hydrostatically driven fans, generators and air conditioning units, control of convertible car top covers and central locking systems.

#### Directions for use:

- Always follow the vehicle manufacturer's recommendations when adding EXT Fluid.
- Check vehicle handbook if in doubt.
- Keep fluid clean.
- Caution: Store only in its original container.
- Keep container clean and tightly closed.
- Do not refill container or use for other liquids.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 02-03-2021