



High Performance Bearing Grease

NLGI 2

Typical Inspection Data:

NLGI	2 (Medium)
Colour	Amber
Texture	Smooth
Operating Temperature Range	-10 °C to +150°C
Drop Point	290°C
Worked Penetration @ 25°C	280 mm/10
Prolonged Working - 100,000 Stokes	+20 Max
Roll Stability - 2hrs	30 Max
Emcor Rust Test	0,0
Copper Corrosion (24 hrs @ 100 °C)	1a
Water Washout @ 79°C	10% Max
Oil Separation (168hrs @ 40°C)	6% wt
Timken OK Load	40lbs
4-Ball Weld Load	2800 N
4-Ball Wear Test, 1hr/60kg	0.8 mm
Wheel Bearing Leakage	10 Max
SKF R2F Rig Test, ambient	Pass
Base Oil Viscosity @ 40°C	180 cSt

Product Features:

- Heavy duty lithium complex grease that offers protection over a wide temperature range.
- Suitable for all wheel bearings.
- Excellent anti-wear and extreme pressure properties for longer bearing life.
- Suitable for automatic and industrial applications.

Handling:

- Avoid extremes of temperature.
- Store under cover.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 30-03-2021